## **KOHLER** Faucets

### **Components®**

Rite-Temp® shower valve trim
K-TS78015-4

#### **Features**

- Includes faceplate and lever handle
- A single handle controls both on/off activation and temperature setting
- Pressure-balancing diaphragm technology maintains outlet temperature within +/-3°F during water pressure fluctuations
- Antiscald protection
- Supplied with metal Industrial handle
- Coordinates with Components faucets, accessories, and showering components to complete your bathroom



- Premium material construction with metal handle ensures reliability and durability
- KOHLER finishes resist corrosion and tarnishing

#### Installation

 Trim only; requires valve to complete installation (sold separately)

#### Required Products/Accessories

K-8300 Series Rite-Temp ${\mathbb R}$  Valve Body Rough-ins or

K-2971-KS 3/4" Pressure-balancing Valve

#### Adapters, Rough-in and Extension Kits

10350 Range: 3-5/8" (92 mm) - 4-3/8" (111 mm)

#### **Recommended Products/Accessories**

K-23723 Faucet cleaner



ADA CSA B651 OBC

#### Codes/Standards

ASME A112.18.1/CSA B125.1 ADA ICC/ANSI A117.1 CSA B651 OBC

# KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

#### Available Colors/Finishes

Color tiles intended for reference only.


Color	Code	Description
	CP	Polished Chrome
	BN	Vibrant® Brushed Nickel
	BL	Matte Black
	2MB	Vibrant® Brushed Moderne Brass
	TT	Vibrant Titanium





## **Components®**

Rite-Temp® shower valve trim K-TS78015-4



#### **Technical Information**

All product dimensions are nominal.

Drain included: No

#### **Notes**

Install this product according to the installation instructions.

NOTICE: Risk of product damage. Long screws for installing trim can damage the K-2971-KS valve. Consult the trim installation guide to verify if the thin wall installation kit is needed. Install straight pipe or tube drop of 7" (178 mm) to 18" (457 mm) with single elbow between the valve and the wall-mount spout.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

