

SQMK72-3636 Swanstone Square Tile Shower Wall Kit

Manufactured from Swanstone solid surface


Recommended for high-use traffic areas and commercial surfaces.

(See page 2 for detailed information.)

WARRANTY Limited Lifetime - Residential Limited 25-year - Commercial

FEATURES

- Chamfered-edges on the 12-inch square tile pattern provide the high-end look of travertine.
- No grout to maintain; will not mold or mildew.
- Ideal for remodeling; easier to install than tile panels glue up over existing surface.
- Coordinates with Swanstone bath products.
- Heat resistant-walls can handle steamer units.
- Compression molding means superior durability.



Designed to fit base areas 36" deep or smaller x 36" wide x 72" high or smaller (914 mm x 914 mm x 1829 mm)

SPECIFICATIONS

SQMK72-3636 Swanstone Square Tile Shower Wall Kit

		Base Area	Ship	Ship	Carton	
Model	Part	Designed To Fit	Wt. Lb.	FedEx	Dims. In.	Cu. Ft.
SQMK72-3636		36"D x 36"W x 72-1/2	-	_	42 x 4 x 78	7.6
	(914	mm x 914 mm x 182	9 ((((()			
		(*or smaller)				

Kit Includes: Two side panels, one back panel, two corner soap shelves. Packaging: Each kit is packed in an individual carton.

ACCESSORIES

See page 36 for complete listing of all wall accessories.

COLORS

.....

Solid Colors:

- White (010)
- Bisque (018)
- Bone (037)

Aggregate Colors:

- Arctic Granite (035)
- Baby's Breath (168)
- Barley (091)
- Bermuda Sand (040)
- Canyon (124) 🔊
- Cloud Bone (126)
- Cloud White (125)
- Glacier (121) 🞜
- Golden Steppe (128)
- Gray Granite (042)
- Ice (130)
- Mountain Haze (129)

- Night Sky (012)
- Pebble (072)
- Prairie (122) 🗖
- Tahiti Desert (050)
- Tahiti Gray (053)
- Tahiti Ivory (059)
- Tahiti Matrix (058)
- Tahiti Sand (051)
- Tahiti White (011)
- Tundra (131)
- Our Planet Colors

STANDARDS AND RATINGS

American Society of Testing and Materials (ASTM) E-84: Class A Flame Spread Rating American National Standard Institute—ANSI Z124.6

International Association of Plumbing and Mechanical Officials (IAPMO) - Listed cUPC listed—Certified to CSA Test Standard B45.5 by IAPMO Uniform Plumbing Code (UPC)

For a complete list of tests and results see the Technical Data Sheet.

SUPPORT DOCUMENTS

Installation instructions available at swanstone.com.

MAINTENANCE AND **CLEANING INFORMATION**

Clean regularly with common household liquid cleaners and rinse within five minutes of application. Occasional scrubbing with abrasive cleaners ensures that the original luster will be maintained. **Do not** use "leave on" cleaning products, such as automatic spray shower cleaners. Prolonged contact with harsh chemicals could have an adverse reaction over time and discolor surfaces. Do not use cleaning agents that caution use on acrylic, polyester or plastics.